

Naboo®

MODELS

Models with boiler

- NAEB071 ⚡
- NAGB071 🔥
- NAEB101 ⚡
- NAGB101 🔥
- NAEB072 ⚡
- NAGB072 🔥
- NAEB102 ⚡
- NAGB102 🔥
- NAEB201 ⚡
- NAGB201 🔥
- NAEB202 ⚡
- NAGB202 🔥

Direct steam

- NAEV071 ⚡
- NAGV071 🔥
- NAEV101 ⚡
- NAGV101 🔥
- NAEV072 ⚡
- NAGV072 🔥
- NAEV102 ⚡
- NAGV102 🔥
- NAEV201 ⚡
- NAGV201 🔥
- NAEV202 ⚡
- NAGV202 🔥

Model 071



Model 101



Model 072



Model 102



Model 201



Model 202



Chamber capacity 1/1 GN (530 x 325 mm) 2/1 GN (530 x 650 mm)	Distance between layers (mm)	Number of covers	Total electric power (kW)	Gas versions nominal heating output (kW/kcal)	External dimensions (mm)	Weight (kg)	Power supply voltage
7x1/1	70	50/120	10,5	-/-	875 x 825 x 820 h.	139	3N AC 400V - 50 Hz
7x1/1	70	50/120	0,5	15/12.900	875 x 825 x 820 h.	156	AC 230V - 50 Hz
10x1/1	70	80/150	16	-/-	930 x 825 x 1040 h.	174	3N AC 400V - 50 Hz
10x1/1	70	80/150	1	28/24.080	930 x 825 x 1040 h.	186	AC 230V - 50 Hz
7x2/1 - 14x1/1	70	70/180	19	-/-	1170 x 895 x 820 h.	180	3N AC 400V - 50 Hz
7x2/1 - 14x1/1	70	70/180	1	30/25.800	1170 x 895 x 820 h.	220	AC 230V - 50 Hz
10x2/1 - 20x1/1	70	150/300	31	-/-	1170 x 895 x 1040 h.	240	3N AC 400V - 50 Hz
10x2/1 - 20x1/1	70	150/300	1	40/34.400	1170 x 895 x 1040 h.	235	AC 230V - 50 Hz
20x1/1	63	150/300	31,8	-/-	960 x 825 x 1810 h.	330	3N AC 400V - 50 Hz
20x1/1	63	150/300	1,8	48/41.280	960 x 825 x 1810 h.	345	AC 230V - 50 Hz
20x2/1 - 40x1/1	63	300/500	61,8	-/-	1290 x 895 x 1810 h.	395	3N AC 400V - 50 Hz
20x2/1 - 40x1/1	63	300/500	1,8	80/68.800	1290 x 895 x 1810 h.	465	AC 230V - 50 Hz

7x1/1	70	50/120	10,5	-/-	875 x 825 x 820 h.	117	3N AC 400V - 50 Hz
7x1/1	70	50/120	0,5	12/10.230	875 x 825 x 820 h.	125	AC 230V - 50 Hz
10x1/1	70	80/150	16	-/-	930 x 825 x 1040 h.	142	3N AC 400V - 50 Hz
10x1/1	70	80/150	1	18/15.480	930 x 825 x 1040 h.	180	AC 230V - 50 Hz
7x2/1 - 14x1/1	70	70/180	19	-/-	1170 x 895 x 820 h.	158	3N AC 400V - 50 Hz
7x2/1 - 14x1/1	70	70/180	1	20/17.200	1170 x 895 x 820 h.	220	AC 230V - 50 Hz
10x2/1 - 20x1/1	70	150/300	31	-/-	1170 x 895 x 1040 h.	201	3N AC 400V - 50 Hz
10x2/1 - 20x1/1	70	150/300	1	27/23.220	1170 x 895 x 1040 h.	218	AC 230V - 50 Hz
20x1/1	63	150/300	31,8	-/-	960 x 825 x 1810 h.	260	3N AC 400V - 50 Hz
20x1/1	63	150/300	1,8	36/30.960	960 x 825 x 1810 h.	290	AC 230V - 50 Hz
20x2/1 - 40x1/1	63	300/500	61,8	-/-	1290 x 895 x 1810 h.	345	3N AC 400V - 50 Hz
20x2/1 - 40x1/1	63	300/500	1,8	54/46.440	1290 x 895 x 1810 h.	400	AC 230V - 50 Hz